

**DECLARATION OF PERFORMANCE**

NL Hoekprofiel RG  
FR Cornière RG  
DE Eckwinkel RG  
EN Cornerprofile RG

Art. Nr. **100 2,6**

DoP-Nr.: **WIL100026000**



**EN 13658-1**

Binnenbepiestering  
Enduit intérieur  
Innenputz  
Inside plastering



27/27 rh 11 ev 35

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

Yield (MPA) Re	331
Tensile (MPA) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 0,458 kg	Pc/Pack 20	Size/Pack 60x75x2600	Weight/Pack 9,15 kg	Pack/Pal 176	Size/Pal 880x1020x2600	Weight/Pal 1610,75
-----------------------	---------------	-------------------------	------------------------	-----------------	---------------------------	-----------------------

Declared performance

length	2600	mm
width	27 x 27	mm
thickness	0,405	mm
weight	0,176	kg/m not perforated
aluzinc coating	19,6	µm / side a
	19,3	µm / side b
aluzinc weight	150	gr/m <sup>2</sup>

Authorized representative : CEO	Date : 1/07/2013	Signed : Tom Heyvaert	Tom Heyvaert Waalslan 13 B -9080 Lochristi
---------------------------------	------------------	-----------------------------	--