

DECLARATION OF PERFORMANCE

NL Afstrijkprofiel
FR Guide de plafonnage
DE Putzlehren
EN Gauge profile

Art. Nr. **1806 2,6**

DoP-Nr.: **WIL310026000**



EN 13658-1

Binnenbepiestering
Enduit intérieur
Innenputz
Inside plastering



27/6 vh 35-65

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

Yield (MPA) Re	331
Tensile (MPA) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 0,2 kg	Pc/Pack 40	Size/Pack 45x20x2600	Weight/Pack 8,01 kg	Pack/Pal 350	Size/Pal 880x580x2600	Weight/Pal 2802,8 kg
---------------------	---------------	-------------------------	------------------------	-----------------	--------------------------	-------------------------

Declared performance

length	2600	mm
width	20 x 6	mm
thickness	0,405	mm
weight	0,077	kg/m
aluzinc coating	19,6	µm / side a
	19,3	µm / side b
aluzinc weight	150	gr/m ²

Authorized representative : CEO	Date	1/07/2013	Signed : Tom Heyvaert	Tom Heyvaert Waalstrand 13 B -9080 Lochristi
---------------------------------	------	-----------	-----------------------------	--